Docket No.: 1190-0618PUS1 Application No.: 10/566,728 Page 2 of 10 Reply dated April 8, 2010

Reply to Office Action of January 13, 2010

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A digital recording apparatus comprising:

a data control circuit which receives a digital recording signal;

a memory which is capable of communicating information with the data control

circuit;

an encryption circuit which is capable of communicating information with the data

control circuit, the encryption circuit encrypting the digital recording signal, the

encryption circuit being deactivated before the data control circuit receives the digital

recording signal to be encrypted;

a recording unit which is controlled by the data control circuit, the recording unit

recording the digital recording signal on a recording medium; and

a recording signal processing circuit which causes the data control circuit to control

transmission of the digital recording signal;

wherein when the digital recording signal needs to be encrypted, the encryption

circuit begins to start up and the digital recording signal is transmitted from the data

control circuit to the memory to be stored in the memory during start-up of the encryption

circuit, and when the encryption circuit becomes capable of operation, the digital

recording signal stored in the memory is transmitted via the data control circuit to the

encryption circuit and is encrypted by the encryption circuit to be recorded in the

recording unit, and

when the digital recording signal needs to be encrypted, the memory secures a

vacant capacity larger than a capacity capable of storing the digital recording signal from

Application No.: 10/566,728 Docket No.: 1190-0618PUS1
Reply dated April 8, 2010 Page 3 of 10

Reply to Office Action of January 13, 2010

a time when the digital recording signal needs to be encrypted to a time when the

encryption circuit becomes capable of operation.

2. (Currently amended) A digital reproducing apparatus comprising:

a reproducing unit which reproduces a digital recording signal from a recording

medium:

a data control circuit which controls the reproducing unit and outputs a reproduced

digital recording signal;

a memory which is capable of communicating information with the data control

circuit;

a decryption circuit which is capable of communicating information with the data

control circuit, the decryption circuit decrypting the digital recording signal, the

decryption circuit being deactivated before the data control circuit receives the digital

recording signal to be decrypted; and

a recording signal processing circuit which causes the data control circuit to control

transmission of the digital recording signal;

wherein when the digital recording signal encrypted and recorded on the recording

medium needs to be decrypted and reproduced, during start-up of the decryption circuit,

the digital recording signal having been stored before start-up of the decryption circuit is

outputted via the data control circuit, and when the decryption circuit is capable of

operation, the digital recording signal read by the reproducing unit is transmitted via the

data control circuit to the decryption circuit and is decrypted by the decryption circuit to

be outputted, and

BIRCH, STEWART, KOLASCH & BIRCH, LLP

DRA/DPC/lab

Application No.: 10/566,728 Docket No.: 1190-0618PUS1
Reply dated April 8, 2010 Page 4 of 10

Reply to Office Action of January 13, 2010

when the digital recording signal needs to be decrypted, the amount of data of the

digital recording signal stored is not less than an amount of data outputted from a time

when the digital record signal needs to be decrypted to a time when the decryption unit is

capable of operation.

3. (Previously Presented) A digital recording/reproducing apparatus comprising:

the digital recording apparatus of claim 1; and

a digital reproducing apparatus comprising:

a reproducing unit which reproduces a digital recording signal from a

recording medium;

a data control circuit which controls the reproducing unit and outputs a

reproduced digital recording signal;

a memory which is capable of communicating information with the data

control circuit:

a decryption circuit which is capable of communicating information with the

data control circuit, the decryption circuit decrypting the digital recording signal,

the decryption circuit being deactivated before the data control circuit receives the

digital recording signal to be decrypted; and

a recording signal processing circuit which causes the data control circuit to

control transmission of the digital recording signal;

wherein when the digital recording signal encrypted and recorded on the

recording medium needs to be decrypted and reproduced, during start-up of the

decryption circuit, the digital recording signal having been stored before start-up of

Application No.: 10/566,728 Docket No.: 1190-0618PUS1
Reply dated April 8, 2010 Page 5 of 10

Reply to Office Action of January 13, 2010

the decryption circuit is outputted via the data control circuit, and when the

decryption circuit is capable of operation, the digital recording signal read by the

reproducing unit is transmitted via the data control circuit to the decryption circuit

and is decrypted by the decryption circuit to be outputted.

4. (Currently amended) An encryption apparatus comprising:

a storage unit which stores a digital signal;

an encryption unit which encrypts the digital signal;

an encryption key generation unit which generates an encryption key for enabling

the encryption unit;

a determination unit which determines whether or not the digital signal needs to be

encrypted by the encryption unit, the encryption unit being deactivated before the

determination unit determines that the digital signal needs to be encrypted; and

a control unit which controls the storage unit and the encryption unit in such a way

that when the determination unit determines that the digital signal does not need to be

encrypted, the digital signal is not encrypted by the encryption unit and the digital signal

stored in the storage unit is outputted, and when the determination unit determines that the

digital signal needs to be encrypted, the digital signal from a time of the determination to

a time when the enabling of the encryption unit is completed by the encryption key is

stored in the storage unit and is encrypted by the encryption circuit to be outputted after

the enabling of the encryption unit is completed, wherein

when the determination unit determines that the digital signal needs to be

encrypted, the storage unit secures a vacant capacity larger than a capacity capable of

 Application No.: 10/566,728
 Docket No.: 1190-0618PUS1

 Renly dated April 8, 2010
 Page 6 of 10

Reply to Office Action of January 13, 2010

storing the digital signal from a time of the determination to a time when the enabling of

the encryption unit is completed by the encryption key.

5. (original) The encryption apparatus according to claim 4, wherein the

encryption key is generated from information read from a recording medium for recording

the digital signal.

6. (Canceled)

7. (Currently amended) A decryption apparatus comprising:

a storage unit which stores a digital signal;

a decryption unit which decrypts an encrypted signal of the digital signal;

an encryption key generation unit which generates an encryption key for enabling

the decryption unit;

a determination unit which determines whether or not the digital signal needs to be

decrypted by the decryption unit, the decryption unit being deactivated before the

determination unit determines that the digital signal needs to be decrypted; and

a control unit which controls the storage unit and the decryption unit in such a way

that when the determination unit determines that the digital signal does not need to be

decrypted, the digital signal is not decrypted by the decryption unit and the digital signal

stored in the storage unit is outputted, and when the determination unit determines that the

digital signal needs to be decrypted, the digital signal from a time of the determination to

a time when the enabling of the decryption unit is completed by the encryption key is

stored in the storage unit and is decrypted by the decryption circuit to be outputted after

DRA/DPC/lab

Application No.: 10/566,728 Docket No.: 1190-0618PUS1
Reply dated April 8, 2010 Page 7 of 10

Reply to Office Action of January 13, 2010

the enabling of the decryption unit is completed, wherein

when the determination unit determines that the digital signal needs to be

decrypted, the amount of data of the digital signal stored in the storage unit is not less than

an amount of data outputted from a time of the determination to a time when the enabling

of the decryption unit is completed by the encryption key.

8. (original) The decryption apparatus according to claim 7, wherein the

encryption key is generated from information read from a recording medium for recording

the digital signal.

9. (Canceled)

10. (Currently amended) An encryption method comprising the steps of:

storing a digital signal;

encrypting the digital signal;

generating an encryption key for enabling a function of encrypting the digital

signal; and

determining whether or not the digital signal needs to be encrypted;

wherein when the determination is that the digital signal does not need to be

encrypted, the digital signal is not encrypted and the stored digital signal is outputted, and

when the determination is that the digital signal needs to be encrypted, the digital signal

when the determination is that the digital signal areas is a supply of

from a time of the determination to a time when the function of encrypting is enabled is

stored and is encrypted to be outputted after the enabling of the function of encrypting is

completed, and

Application No.: 10/566,728 Docket No.: 1190-0618PUS1

Reply dated April 8, 2010 Page 8 of 10

Reply dated April 8, 2010 Reply to Office Action of January 13, 2010

when the determination is that the digital signal needs to be encrypted, a vacant capacity larger than a capacity capable of storing the digital signal from a time of the

determination to a time when the function of encrypting is enabled is secured.

11. (Currently amended) A decryption method comprising the steps of:

storing a digital signal;

decrypting an encrypted digital signal of the digital signal;

generating an encryption key for enabling a function of decrypting the digital

signal; and

determining whether or not the digital signal needs to be decrypted;

wherein when the determination is that the digital signal does not need to be

decrypted, the digital signal is not decrypted and the stored digital signal is outputted, and

when the determination is that the digital signal needs to be decrypted, the digital signal

from a time of the determination to a time when the function of decrypting is enabled is

stored and is decrypted to be outputted after the enabling of the function of decrypting is

completed, and.

when the determination is that the digital signal needs to be decrypted, the amount

of data of the digital signal stored is not less than an amount of data outputted from a time

of the determination to a time when the function of decrypting is enabled.